



LINEA CASA
PORTONI GARAGE
LINEA INDUSTRIALE
CHIUSURE AUTOMATICHE
SICUREZZA LOGISTICA



STRIP BARRIER “STRIPE” - Technical Specifications of standard configuration

- Strip barrier in transparent PVC strips (extruded and with rounded edges), cooled in flat to ensure perfect levelling. Special plasticizers are added to the PVC to guarantee constant flexibility and transparency.
- Strips with full or partial overlapping.
- Excellent solution for any area, no matter how large.
- It allows easy access for both people and vehicles.
- It guarantees good heat and noise insulation.
- It's very useful to separate working areas from dust, smoke, steam, fumes, etc..
- According to environment and/or insulation needs, barriers can be made up to 200-300-400 mm. width strips, and 2-3-4 mm. of thickness.
- The anchorage supports include galvanised steel jaws (also AISI 304 stainless steel for 200 mm. strips) with 180° oscillation around the support bar so that the strips always undergo tensile stress as opposed to shearing stress, ensuring long life to the barrier.
- The “STRIPE” barriers can be supplied with a special rail provided with sliding runners on ball bearings (200 mm. strips apart). The strips can all be moved to one side or divided in two sections to move to each side of the opening.
- The “STRIPE” barrier is just right for closing an opening through which an overhead crane has to travel. It prevents loss of heat and guarantees protection from weather (wind, rain, etc...).